

nola®



Kyrkbänken Bench

Design White Arkitekter

These wooden benches were designed to provide contemporary outdoor seating for public space developments. Designed with timelessness in mind, the benches were crafted with elegance and simplicity. The benches are made in three heights which can be combined to create unique seating arrangements.

Dimensions and weight

Length: 140,5 cm
Width: 50 cm
Height: 35 / 45 / 55 cm

Individual dimensions

The steel plate in the frame: 5 mm thick
Wood components: 40 mm x 92 mm.

Product numbers and combinations

Ö50-00LG Bänk Kyrkbänken låg, höjd 35 cm.
Ö50-00MG Bänk Kyrkbänken mellan, höjd 45 cm.
Ö50-00HG Bänk Kyrkbänken hög, höjd 55 cm.

Append to product number

WOOD AND FINISH

RAL 7047

C for any color other than standard, starting cost is added.

METAL SURFACE FINISH

RAL 7047

C for any color other than standard, starting cost is added.

INSTALLATION TYPE

N for surface mount.

Standard colours



RAL 7047

Materials and surface treatments

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Water-based glaze

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

Assembly and placement

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Fully assembled.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Water-based glazed pine

Products in varnished pine must be maintained regularly with alkyd paint.

Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

The low version is 35 cm high.

The medium version is 45 cm high.

The high version is 55 cm high.

Designers

White Arkitekter

White Arkitekter is one of Sweden's leading architectural offices. With a focus on sustainable architecture, design and city planning, they aim to work for both the current and future generation. White Arkitekter's aim is to through architecture be able to drive the transition towards a sustainable life.



