

nola®



Gå-City Double-sided Bench

Design Tema

Gå-City is a sleek contemporary outdoor bench that makes a striking complement to modern architecture. The bench is uniquely inclusive as it provides an attractive perch for people of all ages. Gå-City offers a flat expanse of space where youths can cluster and children can play. An angled backrest and easy-grip armrest provide extra stability for those needing support when rising to their feet.

Dimensions and weight

Length: 400 cm
Width: 100 cm
Height: 46 / 85 cm
Vikt: 530 kg

Individual dimensions

The base supports are made from 15 mm solid steel fitted with parts made from 5 mm thick steel

Seat slats: 81 mm x 82 mm and 31 mm x 32 mm respectively

Product numbers and combinations

U30-00 Gå-city bench with half backrest

B11-06 Startup cost for powder coating steel in a color other than standard.

Append to product number

WOOD AND FINISH

MH for oiled mahogany.

METAL SURFACE FINISH

A for dark grey RAL 7016.

B for dark brown RAL 8016.

C for any color of steel other than, at additional cost.

INSTALLATION TYPE

M for installation in pre-cast foundations.

Standard colours



RAL 8016

RAL 7016

Materials and surface treatments

Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Installation in pre-cast foundations

Posts for installation in pre-cast foundations.

Delivered pre-assembled.

Maintenance

Oiled mahogany

Oiled mahogany should be oiled two times a year.

Powdercoated steel

Products that are electro-galvanized and powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

The bench has a half backrest and a fully assembled armrest.

Character

A sleek contemporary outdoor bench that makes a striking complement to modern architecture.

Designers

Tema

