



Kwai Bench

Design Eero Koivisto

This attractive, award-winning indoor bench can create a focal point, yet it is discreet enough to blend into the background. The bench is designed in an elegant expression with slats that taper to thinner widths at the edge. The steel frame slightly lifts the wooden parts and makes the appearance of the bench seem even lighter.

Can be treated with Protega Novatherm fire protection, which is a waterborne fire protection paint, for products which, for example, will be placed in connection with escape routes and entrances.



Can be treated with fire protection

Dimensions and weight

Length: 180 cm
Width: 40 cm
Height: 46 cm
Vikt: 23 kg

Individual dimensions

Seat: 10/40 x 192 mm
Steel frame: 35 x 15 x 1,5 mm

Product numbers and combinations

U13-30 Kwai bench
U13-31 Attachment hardware set of 2
B11-06 Startup cost for powder coating steel in a color other than standard.

Append to product number

WOOD AND FINISH

EK for oiled oak.

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

VARIANTS

Can be treated with fire protection, at additional cost.
For fire protection treatment contact Nola.

Standard colours



RAL 9005

Materials and surface treatments

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Fully assembled.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Character

A striking bench with immediate appeal, yet discreet enough to blend into the background.

Designers

Eero Koivisto

