

nola®



Nordfjell Collection Pergola Arch

Design Nordfjell Collection

Pergola Arch is a freestanding arch designed for public parks and open courtyards. Pergola Archs can be installed individually to create an entrance to a designated area, or installed as a series to demarcate a long path. The design provides an ideal structure for climbers and creeper vines, creating greenery and shade. Pergola Arch is produced in laser-cut, powder-coated steel in matt black.

Dimensions and weight

Width: 200, 225, 240 alt 350 cm
Height: 250 alt 280 cm
Depth: 60 alt 69 cm

Product numbers and combinations

V02-01 Arch, pergola arch wall model, flat steel. H: 250 cm, W: 225 cm, D: 60 cm
V02-02 Arch, pergola arch, flat steel. H: 280 cm, B: 240 cm, D: 60 cm
V02-03 Arch, pergola arch, flat steel. H: 250 cm, B: 200 cm, D: 60 cm
V09-05/1 1 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)
V09-05/2 2 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)
V09-05/3 3 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)
V09-05/4 4 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)
V09-05/5 5 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)
V09-05/6 6 LED spotlights, everything included (fittings, drilling and socket for assembly, drive, and connection)

Append to product number

METAL SURFACE FINISH

VFZ for hot-dip galvanized steel only.

G for powder coated gray Gris 2150 Sablé.

S for powder coated black Gris 2200 Sablé.

C for any color other than standard, starting cost is added.

VARIANTS

4 spotlight armatures, 2 drives, drilling and connection is included, as standard, then you can buy 1-6 spotlights separately that is already connected.

INSTALLATION TYPE

M for installation in pre-cast foundations.

Standard colours



Gris 2150 Sablé



Noir 2200 Sablé



Hot-dip galvanized steel

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Installation in pre-cast foundations

Posts for installation in pre-cast foundations.

Levereras monterad för fastbultning mot mark alternativt vägg. Bult ingår ej.

Pergola Arch kan på begäran levereras med kranbil för uppställning på plats.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Hot dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

1st väggfast modell samt 3st markfasta.

För Pergola Arch med LED belysning gäller följande:

Ellucka för kopplingsdon transformator i bågens nedre del.

Ljuspunkter med infälld LED-belysning i bågens horisontella del.

Designers

Nordfjell Collection



