

nola®



## Nordfjell Collection Planter

### Design Nordfjell Collection

A modern and elegant trellis for wall or pergola. Perfect as a support for roses or climbing plants.

Dimensions and weight	Width: 120cm Height: 210/250cm Depth: 120cm (väggspaljé Trellis )
Product numbers and combinations	<p><b>V05-00VFZ-V</b> Portal trellis Chelsea 2007 for wall 210 x 120 cm, VFZ</p> <p><b>V05-00VFZ-P</b> Freestanding portal trellis Chelsea 2007 for wall 250 x 120 x 120 cm, VFZ</p> <p><b>V05-00VFZ-F</b> Freestanding portal trellis Chelsea 2007 250 x 120 x 120 cm, VFZ</p> <p><b>B11-07</b> Extra cost for powder coating of Chelsea and freestanding Chelsea portal trellis</p> <p><b>Append to product number</b></p> <p><b>METAL SURFACE FINISH</b></p> <p>VFZ for hot-dip galvanized steel.</p> <p>C for any color other than standard, starting cost is added.</p>
Standard colours	<div> <div data-bbox="555 806 587 840" style="display: inline-block; width: 15px; height: 15px; background-color: #808080; margin-right: 5px;"></div> Gris 2150 Sablé </div> <div> <div data-bbox="555 842 587 875" style="display: inline-block; width: 15px; height: 15px; background-color: #333333; margin-right: 5px;"></div> Noir 2200 Sablé </div> <div> <div data-bbox="555 878 587 911" style="display: inline-block; width: 15px; height: 15px; background-color: #cccccc; margin-right: 5px;"></div> Hot-dip galvanized steel </div>
Materials and surface treatments	<p><b>Steel</b></p> <p>Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.</p> <p><b>Powder coating</b></p> <p>Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.</p> <p><b>Hot-dip galvanized</b></p> <p>Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.</p>
Assembly and placement	<p>Levereras monterad. Justerbara fästen mot vägg och mark ingår. Bult mot mark/vägg ingår ej.</p>
Maintenance	<p><b>Powdercoated steel</b></p> <p>Products that are powder-coated can be touch-up painted with alkyd paint.</p> <p><b>Hot dip galvanized steel</b></p> <p>Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".</p> <p><u><a href="https://nola.se/en/care-and-maintenance">Read more in our general maintenance advice at nola.se/en/care-and-maintenance</a></u></p>

## Designers

---

### Nordfjell Collection





