

nola®



## Rondo Litterbin

### Design Inventarrum

As a complement to our own range, we also market products from Danish Inventarrum. Like Nola, Inventarrum works for high design and good thought in the public space. All Inventarrum's wastebaskets and ashtrays are basically stainless, then powder coated. Several of the bins are also available with integrated ashtray, or matching, separate ashtray. Rondo is an easy-care and durable trash can. Opens with a hex key, lifting the lid upwards and releasing the front for easy emptying. The shape of the basket in combination with the thick plate makes it very durable. Information about ARC Brasília bench see product sheet for download during assembly.

## Dimensions and weight

### LK30

Basket height: 47/ 65 cm

Height above ground: 85 cm

Total height: 130 cm

Width including stand: 40 cm

Basket diameter: Ø 28 cm

Volume: 30 L

Weight: 20,5 kg

### LK60

Basket height: 57/ 76 cm

Height above ground: 100 cm

Total height: 145 cm

Width including stand: 48 cm

Basket diameter: Ø 35 cm

Volume: 60 L

Weight: 30 kg

## Product numbers and combinations

DAN59/LK30/G - 30 liter, markfast, varmförzinkade.

DAN59/LK30/P - 30 liter, markfast, varmförzinkad och pulverlackerad.

DAN59/LK60/G - 60 liter, markfast, varmförzinkad.

DAN59/LK60/P - 60 liter, markfast, varmförzinkad och pulverlackerad.

DAN60 - Startkostnad pulverlackering vid order av färre än 4 st papperskorgar.

### Append to product number

INSTALLATION TYPE

M for in-ground.

## Standard colours

### Materials and surface treatments

#### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

#### Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

#### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

## Assembly and placement

### In-ground

Cast in ground.

Monteras på rörstativ.

## Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

## Versions

30 alternativt 60 liter.

## Designers

---

## Inventarium

---

