

nola[®]



11:an Table

Design Axel Bjurström

This outdoor table complements the 11:an chair. Together, the two can provide dining furniture for food & beverage applications. 11:an's tabletop is attached to a three-legged base that folds together for easy storage. Like the chair legs, the table base is painted burgundy, a classic colour that adds elegance to any interior. Whether paired with the 11:an chair or displayed on its own, the table makes a stunning addition to any terrace or garden.

CERTIFICATION

Produkt listad i
Svanens Husportal



SundaHus

Dimensions and weight

Length: 70 cm
Width: 70cm
Height: 73 cm
Weight 12 kg

Product numbers and combinations

U80-28 11:AN table, 70 cm x 70 cm, oiled oak with electroplated steel frame powder-coated in Umbra Grey RAL 7022
B11-06 Startup cost for powder coating steel in a color other than standard. Choose a RAL colour.

Append to product number

WOOD AND FINISH

EK for oiled oak.


METAL SURFACE FINISH

Enter no letter for powder coated steel RAL 7022 grey

R for powder-coated steel RAL 3007 red

C for any color on steel, at an additional cost.

Standard colours



Materials and surface treatments

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Monterat.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Available as a table with accompanying chair. Different colors on stands can be obtained by request.

Character


A table made with a tilting top attached to a three-legged base that enables it to be easily stored when not in use.

Designers

Axel Bjurström

Architect Axel Bjurström graduated from University College of Arts, Crafts and Design (Konstfack) in 2007 and has since worked within the fields of architecture, interior design and product design. Bjurström has been awarded several prizes for his work, including Elle Decorations “Young Talent Award” in 2015 and “Chair of the Year” by iF Design Award. Bjurström has worked with clients such as Nordiska Galleriet, Materia, Design House Stockholm, Karl Andersson & Söner, Klong, and David Design.





©Carlos Valencia -Landskapslaget