



## Andromeda Shelter

Design Bernt Fröderberg

System Utblick är ett flexibelt system i stål och trä för kombination av spaljéer, stolpar och pergolatakt. Förutom de standardiserade modulerna finns det en färdig portik, Andromeda. Stolparna är tillverkade i lackerat stål medan pergolataket är i målat trä. Lämplig utemöbel som även färgmässigt passar in är Kalmar.

**Dimensions and weight**

C-C posts: 160 x 132 cm.

Total: 256 x 215 cm.

Height: 240 cm.

**Product numbers and combinations**

Ö70-62

**Append to product number****WOOD AND FINISH**

GV for grey-white wood.

C for wood any NCS S colour, start-up costs are added.

**METAL SURFACE FINISH**

S for black RAL 9005 on steel.

G for Gris 900 Sablé anthracite gray on steel.

C for steel any RAL colour, start-up costs are added.

**INSTALLATION TYPE**

M for in-ground.

**Standard colours**

RAL 9005



Gris 2150 Sablé

**Materials and surface treatments****Stål:**

Stolpar 108 X 3,6 / 50,8 X 3,0 mm.

Allt stål är blåstrat, elförzinkat, kromaterat och pulverlackerat i svart RAL 9005 eller Gris 900 Sablé antracit grå.

**Trä:**

Överliggare 45x120 mm. Dubbla pergolabommar 120x22 och 95x22 mm.

Allt trä i hyvlad, täcklaserad furu i gråvit NCS 3005-Y50R.

**Steel**

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

**Pine**

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

**Electrogalvanized**

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

#### **Powder coating**

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

#### **Water-based glaze**

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

### **Assembly and placement**

#### **In-ground**

Cast in ground.

Överliggare skruvas mot stolpar med sexkantträskruv, pergolabommar spikas mot överliggare.

Stolpar gjuts 70 cm i mark. Grundläggs på icke tjälskjutande material till frostfritt djup.

### **Maintenance**

#### **Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

#### **Water-based glazed pine**

Products in varnished pine must be maintained regularly with alkyd paint.

Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

**[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)**

### **Versions**

Standardfärger: Andromeda stål RAL 9005 svart eller Gris 900 Sablé antracit grå, virke gråvit NCS 3005-Y50R.

Andromeda stål valfri RAL kulör, virke valfri NCS S kulör, startkostnader tillkommer.

### **Character**

Stilig portik som är en färdig enhet i system Utblick. Ett variationsrikt system med många möjligheter.

## Designers

---

**Bernt Fröderberg**



