
# nola



## Ares Litterbin

### Design Inventarrum

As a complement to our own range, we also market products from Danish <u>Inventarrum</u>, which, like Nola, stands for good design in the public space. All Inventarrum's wastebaskets and ashtrays are basically stainless and powder coated. Several of the bins are also available with integrated ashtray, or matching, separate ashtray. For more information about Ares, see product sheet for download during assembly.



Ø 46 cm

Dimensions and weight	Width: 46 cm, indragen sockel 42 cm Height: 115 cm (inklusive sockeln som är 10 cm hög) Ø: 46 cm 75 liters. Can also be in an XL variant on request, which then holds 100 litres. Inner container of hot-dip galvanized steel 0.75 mm.	
Product numbers and combinations	Inventarrum Ares papperskorg	Ares without ashtray for floor mounting, top in polished stainless steel, basket and base in stainless steel. Startup cost for powder coating steel in a color other than standard. Choose a RAL colour.
	för pulverlack	Ashtray complement to litter bin Ig Choose your desired RAL colour. Ig Choose your desired concrete for base.
	Append to product number	
	METAL SURFACE FINISH	
	C for any color other than standard, starting cost is added.	
	INSTALLATION TYPE N for surface mount.	
Standard colours		
Materials and surface treatments	<ul> <li>Stainless steel</li> <li>Stainless steel is an iron alloy with at least 10.5% chromium that often has good resistance to corrosion (rust) and other chemical attacks. A common misconception about stainless steel is that it does not rust at all; it can in fact corrode, especially in environments near the sea with high humidity.</li> <li>Powder coating</li> <li>Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and</li> </ul>	

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

#### Assembly and placement

Surface mount<br/>Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts<br/>not included.MaintenancePowdercoated steel<br/>Products that are powder-coated can be touch-up painted with alkyd paint.<br/>Read more in our general maintenance advice at nola.se/en/care-and-<br/>maintenanceExamples75 liter alt 100 liter (på förfrågan)

#### Designers

#### Inventarrum

