

nola®





Gefle Bollard


Design Nola

The Gefle bollard is embedded with LED lighting to softly illuminate the area around it. A subtle pattern cut into the steel is made visible by the LED lighting integrated into the bollard. Gefle lights the way for pedestrians, shoppers and dog-walkers while creating a barrier that motorists can easily see. LED lighting uses much less electricity than conventional lighting, making Gefle a sound choice for sustainable environments.

FEATURES

 Designed for accessibility

 Lighting included

| | |
|----------------------------------|--|
| Dimensions and weight | <p>Height: 100 cm</p> <p>Ø: 19,4 cm</p> <p>Diameter: 19.4</p> <p>Height above ground: 1.04 m</p> |
| Product numbers and combinations | <p>Ö03-84MB Pollare Gefle</p> <p>Append to product number</p> <p>VARIANTS</p> <p>T = Arrow-shaped finial</p> |
| Standard colours | <p> RAL 9005</p> |
| Materials and surface treatments | <p>The bollard is made in steel powder-coated in standard colour black.</p> <p>The top is made of cast aluminium. The lighting unit contains LEDs and electric cables.</p> <p>Recycled sand cast aluminium</p> <p>Aluminium recycled from scrap, hand cast in sand moulds. The energy consumption when producing recycled aluminium is about 5% of that used when producing virgin aluminium.</p> <p>Steel</p> <p>Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.</p> <p>Powder coating</p> <p>Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.</p> |
| Assembly and placement | <p>Some assembly required. A qualified electrician is required to connect the lighting unit to the mains electrical supply.</p> <p>The bollard is manufactured with electrical cables drawn through its hollow core. A certified electrician is required to connect the electrical circuits to mains power supply. Please see the installation manual for full details.</p> |
| Maintenance | <p>Sand cast aluminium</p> <p>Maintenance on aluminium is not normally needed, but make sure to wash and keep the material clean. Untreated aluminium develops a matte surface over time.</p> <p>Powdercoated steel</p> <p>Products that are powder-coated can be touch-up painted with alkyd paint.</p> <p><u>Read more in our general maintenance advice at nola.se/en/care-and-maintenance</u></p> |

Versions

Available with a smooth, flat top or an arrow-shaped finial.

Character

This bollard is embedded with LED lighting to illuminate the area around it and provide a barrier that has enhanced visibility at night.

Designers

Nola

