# nola



### Gro Floral Trellis

### Design Mia Cullin

A new addition to the Gro planter series that complements the larger freestanding trellis and the medium-sized attachable trellis designed for the rectangular Gro planter. The trellis is compatible with the Gro planter, but can be combined with a range of sizes and shapes not currently offered by the Gro series. On its own, the trellis provides an eye-catching feature that leads creepers and vines upwards along its metal spines. Combined with a planter, the trellis can create a space divider, or provide a subtle means of screening off a larger area. The trellis is unique in its ability to water the plants around it. A discreet water pipe integrated into the frame connects to a watering system that can be placed in the soil beneath it. Designed to be as functional as it is attractive, the Gro trellis encourages growth as it supports the plant life surrounding it.

CERTIFICATION

BYGGVARU Bedömningen

### Dimensions and weight

Height: 96 cm och 116 cm

Ø: 50 cm Weight 2,5 kg

Thickness: 0.3 cm

#### Individual dimensions

The trellis and the foot plates are made from 3mm steel plate.

The frame is made of pipe Ø15mm x 2 mm.

## Product numbers and combinations

Ö16-04BS Gro floral trellis

#### Append to product number

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

#### Standard colours



## Materials and surface treatments

Zinc plated powder coated steel, painted in RAL 6020. Start-up cost for any RAL colour.

### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

### Assembly and placement

### Freestanding

Freestanding product that is placed directly on the ground.

Mounted.

### Maintenance

### Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-maintenance

Versions	Part of the Gro series of planters.

Character Elegant and spacious floral trellis.

Designers

Mia Cullin

