

nola®



Kalmarsund Park Bench


Design Lars Gunnars


Part of the Kalmar furniture suite, this versatile park bench brings contemporary design and ergonomic form together in an attractive design with a striking profile. Kalmarsund can be ordered as a wall-mounted version or with legs, and is available with armrests or without. The bench can be fitted with a backrest, which has been designed with a slight curve that cradles the back comfortably. The seat has also been designed with comfort in mind, crafted with a slight angle to provide a more comfortable position. Kalmarsund has an extended armrest for increased accessibility.

CERTIFICATION

Produkt listad i
Svanens Husportal  BYGGHÄRLIG
BEGÖMNINGEN

FEATURES

 Designed for accessibility



Dimensions and weight

Width: 187/131cm
 Height: 84cm
 Sitting height: 46cm
 Depth: 57cm

Individual dimensions

Wood components: Seat and backrest: 30 mm x 95 mm and 30 mm x 120 mm
 Back steel/undercarriage: 50 x 12 mm
 Armrest: 50 x 20 x 2mm
 Diameter of legs: 48 mm x 3.2 mm
 Wall bracket: 50 mm x 10 mm

Product numbers and combinations

U11-22 Kalmarsund 3-seated backed bench, ground-mounted
 U11-23 Kalmarsund 2-seated backed bench, ground-mounted
 U11-24 Kalmarsund 3-seated backed bench, attachable version
 U11-25 Kalmarsund 2-seated backed bench, attachable version
 U11-28 Kalmarsund 3-seated backed bench, wall-mounted
 U11-29 Kalmarsund 2-seated backed bench, wall-mounted
 B11-06 Starting cost for powder coating of steel in a color other than standard.
 Choose an RAL color
 B11-07 Starting cost for another color of wood. Choose brown or grey for Linax
 or an NCS color for painted wood. If you want the same color on both steel and
 wood, choose the RAL color for both.

Append to product number

WOOD AND FINISH

EK for oiled oak.

TEA for oiled teak.

A for coated pine, light green NCS S 6010-G10Y, stand dark green RAL 6012.

G for coated pine, stand black RAL9005.

H for coated pine, maroon NCS S 4550-Y80R, stand black RAL 9005.

C for coated pine any color, starting cost is added.

METAL SURFACE FINISH

RAL 9005

C for any color other than standard, at additional cost.


INSTALLATION TYPE

N for surface mount.

M for in-ground.

V for mounted to wall.

Standard colours



Materials and surface treatments

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Teak - FSC-certified

FSC-labeled teak is exceptionally durable in an outdoor environment. Teak has a high content of silicon and tannic acids, which makes it quite expensive to process. If you want to keep the reddish-brown luster, you should oil the wood several times during a season, otherwise it turns gray quickly.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Water-based glaze

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Mounted to wall

Bolted in place to stand/wall bracket.

Bolts for walls not included.

The seat and legs are delivered separately, ready to be assembled with the bolts provided.

Maintenance**Water-based glazed pine**

Products in varnished pine must be maintained regularly with alkyd paint. Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Oiled teak

Teak should be oiled annually to maintain the brown color. Without maintenance, teak takes on a silver gray color over time.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Two- or three-seater. The bench can be ground-mounted, attached to the surface or wall-mounted.

Character

Designed with a slight curve that cradles the back, the backed bench provides a comfortable seat. Kalmarsund has an extended armrest for increased accessibility.

Designers

Lars Gunnars



