

Kalmarsund Furniture Group

Design Lars Gunnars

Kalmarsundserien is a further development of Kalmar Furniture Group. The seating comfort is as good as in Kalmar but the bench and sofa have only two legs that are cast or bolted to the ground.

CERTIFICATION

Produkt listad i Svanens Husportal BYGGNARU BEDÖMNINGEN

Dimensions and weight

Kalmarsund park bench

Width: 187/131cm Height: 84cm Sitting height: 46cm Depth: 57cm

Individual dimensions

Wood components: Seat and backrest: 30 mm x 95 mm and 30 mm x 120 mm

Back steel/undercarriage: 50 x 12 mm

Armrest: 50 x 20 x 2mm

Diameter of legs: 48 mm x 3.2 mm Wall bracket: 50 mm x 10 mm

Kalmarsund armchair

Width: 61 cm Height: 84 cm

Armrest height: 67 cm Sitting height: 46 cm Depth: 57 cm

Weight 32 kg

Individual dimensions

Wood components: Seat and backrest: 30 mm x 95 mm and 30 mm x 120 mm

Back steel/undercarriage: 50 x 12 mm

Armrest: 50 x 20 x 2mm

Diameter of legs: 48 mm x 3.2 mm Wall bracket: 50 mm x 10 mm

Kalmarsund bench

Length: 187 cm Width: 57 cm

Armrest height: 66 cm Sitting height: 46 cm Weight 25 kg

Individual dimensions

Wooden components: Seat: 30 mm x 95 mm Back steel/undercarriage: 50 x 12 mm

Armrest: 50 x 20 x 2mm

Diameter of legs: 48 mm x 3.2 mm

Kalmar Table

Length: 72 cm / 132 cm

Height: 70 cm Depth: 72 cm

Weight 24 kg/32 kg

Individual dimensions

Wood parts: 30 mm x 70 mm / 30 mm x 95 mm

Flat oval steel parts: 20 mm x 50 mm Flat steel base: 10 mm x 60 mm Pipe steel legs: Ø: 50 mm

Flat steel base plate: 12 mm x 60 mm

Product numbers and combinations

B11-06 Starting cost for powder coating of steel in a color other than standard.

Choose an RAL color

B11-07 Starting cost for another color of wood. Choose brown or grey for Linax or an NCS color for painted wood. If you want the same color on both steel and wood, choose the RAL color for both.

U11-19	Kalamarsund 3-seated backed bench without armrests, In-ground

<u>U11-22</u> <u>Kalmarsund 3-seated backed bench, ground-mounted</u> <u>U11-23</u> <u>Kalmarsund 2-seated backed bench, ground-mounted</u>

<u>U11-24</u> <u>Kalmarsund 3-seated backed bench, attachable version</u>

U11-25 Kalmarsund 2-seated backed bench, attachable version
U11-28 Kalmarsund 3-seated backed bench, wall-mounted

<u>U11-29</u> <u>Kalmarsund 2-seated backed bench, wall-mounted</u>

 U11-26
 Kalmarsund armchair ground-mounted

 U11-27
 Kalmarsund armchair attachable version

 U11-20
 Kalmarsund bench ground-mounted

 U11-21
 Kalmarsund bench attachable version

 U11-04
 Kalmar table 132 x 72 cm

<u>V11-05</u> <u>Kalmar table 72 x 72 cm</u>

<u>U11-05SCH</u> <u>Kalmar table 72 x 72 cm with wood-laminate</u>

<u>U11-01BESLAG</u> Attachment fixtures, set of 4

Append to product number

WOOD AND FINISH

MH for oiled mahogany.

LIN for linax impregnated pine.

E for oiled oak.

A for coated pine, light green NCS S 6010-G10Y.

H for coated pine, maroon NCS S 4550-Y80R.

GRÅ for coated pine, grey NCS S 5502-B

C for coated pine any color, starting cost is added.

METAL SURFACE FINISH

RAL 9005

C for any color other than standard, at additional cost.

INSTALLATION TYPE


N for surface mount.

M for in-ground.

V for mounted to wall.

Standard colours





Materials and surface treatments

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Topcoat

Painted wood is made with D-Dur Pigmented Polyurethane two-component topcoat. The topcoat has good resistance and outdoor durability. Gloss number: 60.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Linax

Linax is a linseed oil-based impregnation that provides extra long durability in outdoor environments and corresponds to impregnation class AB. The impregnated wood turns gray over time, which means that it should be re-oiled if necessary. Use a linseed-based oil for impregnated materials.

After traditional impregnation according to NTR AB, the wood is boiled in a hot linseed oil with or without color pigments under vacuum. The oil is penetrated into the surface on all six sides, which reduces moisture absorption in the wood and gives a dimensionally stable product over time. The result is a dried product with good resistance to rot that also has long maintenance intervals. Linaximpregnated furniture is intended for outdoor environments only.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Mounted to wall

Bolted in place to stand/wall bracket.

Bolts for walls not included.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

Oiled mahogany

Oiled mahogany should be oiled two times a year.

Linax impregnated pine

Outdoor furniture requires oiling every 5 years and panel products and roofs require oiling every 12 years. Maintenance should be done with linseed oil varnish. It is important that the wood is clean and dry (max. 20% moisture content) before it is finished with oil. When washing, do not use high-pressure cleaners. Washing should be done with lukewarm water and then rinsed off with a water hose at normal pressure. Strong grease-dissolving agents should not be used, but washing should be done with a mild household detergent. Detergents containing bleach should also not be used.

The oil can be applied with a roller or brush. Too much oil can cause growth on the wood and give a sticky surface. Attacks by growth can also occur if the wood has not been sufficiently dry or cleaned before the oil is applied. Growth does not damage the wood and is relatively easy to remove, but has a tendency to return.

Topcoat

Products treated with D-Dur Pigmented polyurethane two-component topcoat should be maintained regularly. Maintenance intervals approx. 1 time per year. Damage and cracks should be repaired immediately. Touch-up paint with, for example, Nordsjö One door and window water-based topcoat.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-

maintenance

Designers

Lars Gunnars









