

nola®



Kvadrat Litterbin

Design Eva Herdin

The Kvadrat litterbin is an efficient, flexible design that can be complemented by an ashtray from the same series. The sides are perforated with a repeating pattern of square-shaped holes. The litterbin is available with an opening in the top or on the side, or fitted with a lid. Kvadrat can be wall-mounted or supplied with an attachable post that attaches to a freestanding concrete base.

CERTIFICATION



Dimensions and weight

Basket diameter: Ø 33 cm
Height including lid: 54 cm
Overall height including post: 81 cm
Height basket including lid: 72 cm
Volym: 42 L
Weight of wall-mounted version: 12 kg
Weight of attachable version with post: 15 kg
Weight of concrete base: 23 kg

Kvadrat ashtray

Diameter: Ø 15 cm
Height: 24 cm
Support post height above ground: 76 cm
Height including support post: 80 cm
Weight: 2.5 kg
Vikt supporting post: ca 3,5 kg depending on attachment
Weight of concrete base: 23 kg

Rain cover

Total height: 46 cm
Height above ashtray: 22 cm
Width: 20 cm

Product numbers and combinations

Ö16-64T Kvadrat papperskorg med helt lock, inkl. stolpe med fotplatta för golvmontage.
Ö16-64TM Kvadrat papperskorg med helt lock, inkl. stolpe för fastgjutning.
Ö16-64TV Kvadrat papperskorg med helt lock, inkl. väggfäste.
-
Ö16-65T Kvadrat papperskorg med öppet lock + askkopp inkl. stolpe med fotplatta för golvmontage.
Ö16-65TM Kvadrat papperskorg med öppet lock + askkopp inkl. stolpe för fastgjutning.
-
Ö16-66T Kvadrat papperskorg med helt lock + askkopp inkl. stolpe med fotplatta för golvmontage.
Ö16-66TM Kvadrat papperskorg med helt lock + askkopp inkl. stolpe för fastgjutning.
-
Ö16-67T Kvadrat papperskorg med öppet lock inkl. stolpe med fotplatta för golvmontage.
Ö16-67TM Kvadrat papperskorg med öppet lock, inkl. stolpe för fastgjutning.
Ö16-67TV Kvadrat papperskorg med öppet lock, inkl. väggfäste.
-
Ö16-70K Kvadrat "Östersundsmodellen".
-
Ö16-63 Betongfot, fristående. Används tillsammans med stolpe med fotplatta.
Ö16-63S/90 Stolpfäste Ø 90 mm. För papperskorgar ZigZag och Kvadrat.
Ö16-63S/108 Stolpfäste Ø 108 mm. För papperskorgar ZigZag och Kvadrat.
Ö16-63S/121 Stolpfäste Ø 121 mm. För papperskorgar ZigZag och Kvadrat.

Ö16-68K Kvadrat Askopp inkl. väggfäste

Ö16-69T Stolpe till askkopp Kvadrat med fotplatta för golvmontage.

Ö16-69TM Stolpe till askkopp Kvadrat för fastgjutning.

Append to product number

METAL SURFACE FINISH

U19-38 Startkostnad valfri färg.

Standard colours

 RAL 9005

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Stainless steel

Stainless steel is an iron alloy with at least 10.5% chromium that often has good resistance to corrosion (rust) and other chemical attacks. A common misconception about stainless steel is that it does not rust at all; it can in fact corrode, especially in environments near the sea with high humidity.

Aluminium

Aluminum is a soft light metal that is silvery to gray in color. Depending on the alloy, aluminum usually has good corrosion resistance. It is common for the aluminum to be extruded into tubes or rolled into a plate in the desired material thickness.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Fully assembled.

The attachable version bolts to the post and the post bolts to the floor. The bolt-holes have a diameter of 10 mm for 8 mm bolts. Bolts not included.

The post for the ground-mounted version should be cast 40 cm below ground level.

The wall-mounted version should be bolted to the wall. The bolt-holes have a diameter of 7 mm for 6 mm bolts. Bolts not included. Please refer to the assembly instruction for specific details.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

The litterbin is available with an open top or with a hinged lid, and can be combined with an ashtray. Kvadrat is available in a wall-mounted version or supplied with an attachable post that fits into a freestanding concrete base. The post can also be ground-mounted.

Character

The Kvadrat litterbin is an efficient, flexible and functional design that can be complemented by an ashtray.

Designers

Eva Herdin



'Östersundmodellen' in color RAL 7011



'Östersundmodellen' in color RAL 9005