

nola®



Lean Multi-sided Park Bench

Design NATiON + KSA DESIGN

This multi-sided park bench provides conventional seating on one side and a standing bench for individuals to lean against on the other. The surface between the two can provide space for laptops and other electronic devices to be placed. The bench provides three seats and can be complemented by optional armrests. Lean is designed for use in areas where human traffic can become congested. Lean's streamlined proportions and simplistic style provide maximum seating where space is minimal.

Dimensions and weight

Length: 189 cm
Height: 100 cm
Sitting height: 46 cm
Depth: 370 cm
Weight 121 kg – 130 kg

Product numbers and combinations

U18- Lean komplett soffor i oljad ek 189 cm
05HVE
U18-05AH Lean armstöd höger

U18-05AV Lean armstöd vänster

U18-05AD Lean dubbla armstöd för en sits

U18-05H Lean stativ höger

U18-05M Lean stativ mitt

U18-05V Lean stativ vänster

U18-05E Lean sits och ryggstöd

B11-06 Startkostnad för pulverlackering av stål i en annan färg än standard.
Välj en RAL kulör

Append to product number

WOOD AND FINISH

E for oiled oak.

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

VARIANTS

Lean går att förlänga, använd systemets delar för att få den längd du önskar. För utförligare beskrivning se monteringsanvisningen.

INSTALLATION TYPE

N for surface mount.

Standard colours



Noir 2200 Sablé

Oiled oak

Materials and surface treatments

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Recycled sand cast aluminium

Aluminium recycled from scrap, hand cast in sand moulds. The energy consumption when producing recycled aluminium is about 5% of that used when producing virgin aluminium.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil. Black stains on oiled oak can be removed with oxalic acid.

Powder coated Aluminium

Products that are powder-coated can be touch-up painted with alkyd paint if necessary.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Available with 1 or 2 armrest.

Character

A multi-purpose bench that provides conventional seating on one side and a support for individuals to lean against on the other.

Designers

**NATION +
KSA
DESIGN**



