

nola®



Luma Furniture Group


Design Erik Österlund


Luma is an extensive furniture series with a large variety of design options. With its softly rounded wooden slats and streamlined steel parts, Luma is a durable and contemporary outdoor design. Luma is available in a range of lengths and can be customised according to the requirements of site it is intended for. The seats can be installed on top of concrete plinths, on stone walls or as freestanding seats. Luma can also be cut on the diagonal to create angles at each end.

CERTIFICATION

Produkt listad i
Svanens Husportal   **SundaHus**

FEATURES

 Designed for accessibility

 Can be mounted on wall

Dimensions and weight

Luma Park Bench

Length: 180 cm / 260 cm

Width: 48 cm

Height: 76 cm

Sitting height: 46 cm

Enskilda dimensioner

The steel supports underneath: 80 x 50 x 2 mm

The flat steel parts forming the seat and backrest: 60 x 8 mm

Wood components: 32 x 56 mm

Optional tabletop: Thickness: 6 mm

Luma & Luma Titan Bench

U18-35 Luma Bench 180 cm

Height: 46 cm

Length: 180 cm

Width: 42 cm

U18-37 Luma Bench 260 cm

Height: 46 cm

Length: 260 cm

Width: 42 cm

U18-45 Luma Titan 180 cm

Height: 46 cm

Length: 180 cm

Width: 80 cm

U18-47 Luma Titan 260 cm

Height: 46 cm

Length: 260 cm

 Width: 80 cm

260 cm bench have 3 st stands.

Armrest Luma: Width: 5 cm

Tabletop: Height over seat: 23 cm. Ø: 30 cm

Individual dimensions

The steel supports underneath Luma: 60 x 50 mm

The flat steel parts Luma: 60 x 8 mm

The steel supports underneath Luma Titan: 120 x 60 mm

The flat steel parts Luma Titan: 70 x 8 mm

Tabletop: Thickness: 6 mm

Product numbers and combinations

B11-05 Additional fee for non-standard wood

B11-06 Additional fee for choosing a non-standard colour on steel

U18-48/180 Luma park bench 180 cm

U18-48/260 Luma park bench 260 cm

U18-49R Luma armrest

U18-35/BORD Attachable tabletop

U18-35 Luma bench length 180 cm

U18-37 Luma bench length 260 cm
U18-39 Luma bench, custom-made length to a maximum of 260 cm
U18-35-ARM Luma bench armrest
U18-45 Luma Titan bench length 180 cm
U18-47 Luma Titan bench length 260 cm
U18-35/BORD Luma attachable tabletop 30 cm

Append to product number

WOOD AND FINISH

EK for oiled oak.

METAL SURFACE FINISH

C for any color other than standard, starting cost is added.

INSTALLATION TYPE

N for surface mount.

M for in-ground.

V for mounted to wall.

MUR for mounted on wall.

Standard colours



RAL 7011

Oiled oak

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

Surface mount

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

Mounted on wall

Frames are attached to concrete or stone walls with expanders or chemical anchors. Seat sections mounted on top of walls are attached to the frames.

Fasteners for mounting on top of walls not included.

Mounted to wall

Bolted in place to stand/wall bracket.

Bolts for walls not included.

The seats are delivered fully assembled ready for installation to the legs / supports with the screws included in delivery. The bolts required for attaching the seat to the ground, to a concrete plinth or to a stone wall are not included.

Maintenance

Glans 40. Pulverlack går att beställa på sprayflaska.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Luma offers park benches and benches of different lengths that can be customised if required. The ends of the benches can be cut at an angle if needed.

Sustainability**Luma Park Bench**

CO₂-eq: 9,24 kg CO₂

Energy consumption: 1787,75 MJ

Recycled materials: 5,83 %

[View EPD for details](#)

Designers

Erik
Österlund



