

nola®



**Dan 10
Bollard**

Design Inventarium

/

Dimensions and weight

Ø: 11 cm
Weight 14 kg

/

Product numbers and combinations

DAN10-0 Dan 10 pollare utan kedjeögla
DAN10-1 Dan 10 slutstolpe med 1 kedjeögla
DAN10-3 Dan 10 Mellanstolpe med 2 st kedjeöglor

Append to product number

METAL SURFACE FINISH

VFT för endast varmförzinkat.

VFP för varmförzinkat och pulverlackerat samt färgnumret för RAL-färgen.

C för valfri kulör på stål, mot tilläggskostnad.

VARIANTS

Reflex: Ange färg på reflex; vitt, rött eller gult.

INSTALLATION TYPE









A fotplatta som bultas ovanpå mark. (Ej standard) Bultar ingår ej.

B för nedgrävning i mark. Nedgrävningdjup 52cm.

C för prefab betongfundament. Bet.: DAN DK108P.

D för Vingfundament. Bet.: DAN VING108.

Standard colours

	RAL 5011
	RAL 5013
	RAL 6005
	RAL 6009
	RAL 7021
	RAL 7024
	RAL 9005
	RAL 9010

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Hot-dip galvanized

Hot-dip galvanizing provides very strong protection against corrosion. The steel is dipped into a bath of hot liquid zinc. The zinc attaches and creates a surface coating on the steel part, which is then taken out of the bath and drained of excess zinc.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

/

A fotplatta som bultas ovanpå mark. (Ej standard) Bultar ingår ej. B för nedgrävning i mark. Nedgrävningdjup 52cm. C för prefab betongfundament. Bet.: DAN DK108P. D för Vingfundament. Bet.: DAN VING108.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Hot dip galvanized steel

Hot-dip galvanized can be touch-up painted with so-called "cold galvanizing".

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

/

Character

Reflexpollare med utbytbar fundament.

Designers

Inventarium
