



nola®



Parklet Planter

Design Nola

The Parklet planter is a rectangular, easy-care planter designed for Nola's Parklet system. The simplicity of the planter makes it easy to place in a variety of environments and suits plantings of many different types. The vessel is supplied as a unit and includes drainage holes.



Dimensions and weight

Length: 240 cm
 Width: 40 cm
 Height: 43 cm (45 cm med sits)

Product numbers and combinations

Ö06-32 PARKLET planter 2400x450x400 mm
 Ö06-33 PARKLET wooden seat for mounting on planter - provides bench 240 x 40 x 45 cm

Append to product number

METAL SURFACE FINISH
 RAL 7033
 C for any color other than standard, starting cost is added.

Standard colours

 RAL 7033

Materials and surface treatments

Steel
 Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Powder coating
 Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Electrogalvanized
 Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

SiOO:X treatment

Sioo:x is a wood protection with environmentally friendly silicon technology. Water-based and biocide-free. We use Sioo mainly for our oak furniture. Sioo:x treatment of is suitable for all woods, outside as well as inside, and gives a light surface without pigments. The surface is UV-resistant, water-repellent and non-stick. Active and preventive action against algae, mould and pests. Also rot-proof, wood-strengthening and fire-retardant. This wood protection provides long durability and easy maintenance.

Maintenance

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

SiOO:X treatment on coniferous wood

Sioo:x-treated products are treated twice upon delivery; once with a wood protection (Premium Träskydd Altan) and once with a surface protection (Premium Ytskydd Altan). Directly after a product has been installed, it should be treated once more with Sioo:x Premium Surface Protection Altan for best durability. After that, every 12 months. The surface protection forms a wear surface, which means that products that are exposed to severe mechanical wear may need to be treated more often than every ten years. The surface treatment has a tested effect according to the standards EN 46 and EN 113.

For information about the Sioo treatment see the website www.sioox.se.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](http://nola.se/en/care-and-maintenance)

Designers

Nola

