

nola®



## Paxa Furniture Group

### Design Blenda Design

The Paxa outdoor furniture group is considered a masterpiece of materials and form. The table stands on two asymmetrical legs, each balancing the surface weight between them. The benches are designed in sections that combine seamlessly to form extended lengths. Available in smooth concrete or lightweight steel, the choice of legs can make the products appear more robust, or create a streamlined style. The tabletop and seating surfaces are crafted in oiled mahogany, oiled oak or painted pine.

#### CERTIFICATION

Produkt listad i  
Svanens Husportal  BYGGVARU  
BEDÖMNINGEN

## Dimensions and weight

### Paxa bench

Length: Paxa 1: 180 cm / Paxa 2: 180 cm / Paxa 3: 300 cm

Width: Paxa 1: 50 cm / Paxa 2: 90 cm / Paxa 3: 90 cm

Sitting height: 45 cm

Weights of complete benches: Paxa 1: 150 kg Paxa 2: 233 kg Paxa 3: 361 kg

Weights and dimensions of parts: Paxa 1 end section: length: 16 cm weight: 58 kg

Paxa 1 central support: length: 24 cm weight: 72 kg Paxa 1 seat: length: 148 cm height: 11.5 cm weight: 34 kg

Paxa 2 and Paxa 3 end section: length: 16 cm weight: 90 kg Paxa 2 and Paxa 3 central section: length: 24 cm weight: 112 kg.

Paxa 2 seat only length: 148 cm height: 11.5 cm weight: 53 kg

Paxa 3 seat only length: 268 cm height: 11.5 cm weight: 82 kg Dimension of pine slats in seat: 3.2 x 3.2 cm / 3.2 cm x 6.0 cm

Please consult the assembly guidelines to see how the products can be connected and configured.

### Paxa Table

Length: 180 cm

Width: 71 cm

Height: 76 cm

Weight 230 kg

### Paxa Sofa

BENCH 1 (U20-60) Length: 180 cm Height: 45 cm Width: 50 cm Weight: 150 kg

Seat length: 148 cm Seat thickness: 11.5 cm Seat width: 50 cm Seat weight: 34 kg

BENCH 2 (U20-64) Length: 180 cm Height: 45 cm Width: 90 cm Weight: 233 kg

Seat length: 148 cm Seat thickness: 11.5 cm Seat width: 90 cm Seat weight: 53 kg

BENCH 3 (U20-68) Length: 300 cm Height: 45 cm Width: 90 cm Weight: 361 kg

Seat length: 268 cm Seat thickness: 11.5 cm Seat width: 90 cm Seat weight: 82 kg

### Paxa steel bench

Paxa Steel double: Length: 352 cm Height: 45 cm Width: 50 cm Weight: 160 kg

Paxa Steel: Length: 180 cm Height: 45 cm Width: 50 cm Weight: 80 kg

## Product numbers and combinations

U20-60 Paxa 1 complete bench L 180 cm x W 50 cm

U20-60M Paxa 1 complete bench L 180 cm x W 50 cm, legs extended

U20-60TASS Paxa industrial felt floor pads

U20-60R Paxa 1 backrest

U20-60/ARM Paxa 1 armrest for bench

U20-64/ARM Paxa 1 armrest for park bench

U20-64 Paxa 2 complete bench L 180 cm x W 90 cm

U20-68 Paxa 3 complete bench L 300 cm x W 90 cm

**U20-67R** Paxa 2 backrest  
**U20-64/ARM** Paxa 2 and Paxa 3 armrest for pyramid-shaped backrest 34 cm  
**U20-59** Paxa table  
**U20-60** Paxa bench 180 cm, width 50 cm  
**U20-60R** Upright backrest for Paxa bench U20-60  
**U20-60TASS** Industrial felt protector, 1 per frame  
**U20-64R** Paxa 2 park bench length 180 cm, width 90 cm with pyramid-shaped central backrest  
**U20-68R** Paxa 3 park bench length 300 cm, width 90 cm with pyramid-shaped central backrest  
**U20-64/ARM** Paxa armrest for version with backrest  
**U20-74** Paxa Steel bench, extended with central support  
**U20-75** Paxa Steel bench  
**B11-07** Additional fee for choice of non-standard colours on wood

#### Append to product number

#### WOOD AND FINISH

EK for oiled oak.

MH for oiled mahogany.

G for tabletop in glazed pine. NCS S 6000-N (grey).

C for any NCS color other than standard, starting cost is added.

#### VARIANTS




A for frame coloured in antracite

No letter after the article number for light grey natural concrete.

#### INSTALLATION TYPE

M for installation in pre-cast foundations.

#### Standard colours

-  NCS S 6000-N (grå)
-  Ljust grå betong ofärgad
-  Infärgad antracitgrå betong

#### Materials and surface treatments

##### Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

##### Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

##### Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

### **Wood oil**

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

### **Water-based glaze**

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

### **Concrete**

Concrete is cement mixed with crushed stone or aggregate. The material is very strong in compression but fragile in tension. To compensate for this concrete can be reinforced, often with steel.

### **Coloured concrete**

Colored concrete is concrete in a color other than standard grey. Pigment is added to the dry mixture, which means that the concrete becomes coloured throughout. Each color has its own recipe.

## **Assembly and placement**

### **Installation in pre-cast foundations**

Posts for installation in pre-cast foundations.

Delivered in parts for assembly on site.

Freestanding or attachable. The frames are prepared with boltholes for M16 bolts to attach the frame to the surface. Bolts are not included.

## **Maintenance**

### **Oiled oak**

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

### **Oiled mahogany**

Oiled mahogany should be oiled two times a year.

### **Water-based glazed pine**

Products in varnished pine must be maintained regularly with alkyd paint. Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

### **Concrete**

Both normal concrete and fibre-reinforced concrete are sensitive to hard edge impacts. A concrete product that has been damaged can be repaired with polyester filler, such as the product "Plastic Padding".

### **Coloured concrete**

Products made of coloured concrete are washed with a pressure sprayer at low pressure. Damaged products can be repaired with a repair kit that is available to order.

**[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)**

## Versions

The concrete frames are available in standard colour grey, or alternatively, anthracite. The tabletop is available in oiled mahogany, oiled oak or pine painted with alkyd oil enamel. Other types of wood are available upon request.

## Character

Although the Paxa furniture group is striking in its use of materials and form, it has an understated character. Paxa is perfectly suited to contemporary architecture and modern outdoor environments.

## Designers

---

### Blenda Design

Blenda is a designstudio based in Gothenburg, committed to designing furniture for public spaces. With design that works towards both interiors and urban exteriors, they have participated in many projects in the recent years. The products can be found across Sweden, for example in Stavanger Cultural Center, Museum of Modern Art in Stockholm, Arlanda Airport and Gothenburg City library. The studio is run by landscape architect Katarina Gunnarsson and Ingemar Holmlid.

