

nola®



Sjöstad Furniture group


Design Erik Österlund

Sjöstad is an example of public space design at its best. This park bench is designed to provide additional support along the armrests and backrest, providing those who need assistance with an independent means of sitting down and standing up. Sjöstad is made to accommodate a wide range of body types and mobilities, making it an efficient combination of contemporary form and ergonomic design. Sjöstad is also available as a bench and a table.

CERTIFICATION



FEATURES

 Designed for accessibility

Dimensions and weight

Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Sjöstad Park bench

Length: 175 cm

Height: 81 cm

Armrest height: 66 cm

Sitting height: 45 cm

Depth: 55 cm

Weight 45 kg

Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Back slats: 118 x 32 mm

Seat: Wood components: 92 x 32 mm

Sjöstad Table

Length: 140 cm

Width: 68 cm

Height: 73 cm

Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Sjöstad Bench

Length: 148 cm

Height: 46 cm

Sitting height: 46 cm

Depth: 42 cm

Weight 45 kg

Individual dimensions

The front legs: 40 mm x 40 mm

The back legs: 40 mm x 50 mm

The sub-frame is made in square pipe: 30 mm x 60 mm

Back slats: 118 x 32 mm

Seat: Wood components: 92 x 32 mm

Product numbers and combinations

U20-83 4 fastening irons, stainless steel

B11-06 Startup cost for powder coating steel in a color other than standard.

Choose a RAL colour.

U20-80 Sjöstad backed bench

U20-82 Sjöstad table

U20-81 Sjöstad bänk

Append to product number

WOOD AND FINISH

EK for oiled oak.

MH for oiled mahogany.

A for painted pine in RAL 8028.

METAL SURFACE FINISH

Gris Sablé 2900 är standard on steel.

C for any color other than standard, starting cost is added.

Choose a RAL colour.

Standard colours

-  RAL 8028
-  Gris 2900 Sablé
-  Oiled oak
-  Oiled mahogany

Materials and surface treatments

The seat and backrest or made in painted pine in RAL 8028, oiled oak or FSC-mahogany

The sub-frame and all legs are made in square pipe. All steel is zinc-electroplated and powder-coated. All screws are stainless steel. The standard colour is anthracite grey, Gris 900 Sablé.

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Mahogany - FSC-certified

FSC-marked mahogany is a wood with good durability in the outdoor environment. In addition, it retains its color tone better than, for example, oak and teak. Mahogany lives and moves, sometimes more than teak.

Oak

Oak is a heavy, hard and medium tough wood. Moderately dimensionally stable in case of moisture changes. Oak wood blackens if it is exposed to moisture or wetness for a long time. However, it does not affect the other properties of the wood. Thanks to its hardness and toughness, the oak wood is suitable for furniture and other use in exposed environments.

Wood oil

Wood oil provides good protection against the stresses of the outdoor climate and at the same time highlights the wood's natural appearance and properties.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Partly assembled. The seat and backrest should be attached to the frame with enclosed bolts.

Maintenance

Oiled oak

Oiled oak should be oiled twice a year for best protection. Good maintenance can never completely prevent stains from occurring, but oak that is not maintained will turn blacker and turn gray faster, but it still has a very long life. When re-oiling products, a finely boiled oil that penetrates the wood should be chosen over a film-forming oil.

Oiled mahogany

Oiled mahogany should be oiled two times a year.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

Teak on pine, oiled oak or FSC- mahogany.

Character

Sjöstad provides additional support along the armrests and backrest, giving those who need assistance an independent means of sitting down and standing up.

Designers

Erik
Österlund



