

nola®



## Slingan Ashtray

Design Gunilla Hedlund

Slingan's spiraling form resembles an architectural detail more than an ashtray. Slingan can be mounted to a wall or fixed to a freestanding support. Its unique shape complements rounded structures such as columns and posts, or provides a striking contrast to flat surfaces and right angles. A discreet flap in the ashtray's underside opens to empty the contents.

## Dimensions and weight

Height: 32 cm  
Ø: 18 cm  
Weight 4,8 kg

Frame: Height: 108 cm Weight: 12.5 kg.

### Individual dimensions

The stainless steel sheet in the cylinder is 2 mm thick. The steel in the frame is 4 mm thick.

## Product numbers and combinations

Ö15-01

Ö15-01N SLINGAN ashtray with support post, stainless steel with post lacquered in Jet Black RAL 9005, attachable

### Append to product number

INSTALLATION TYPE

N for surface mount.

V for mounted to wall.

## Standard colours

 RAL 9005

## Materials and surface treatments

### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

### Stainless steel

Stainless steel is an iron alloy with at least 10.5% chromium that often has good resistance to corrosion (rust) and other chemical attacks. A common misconception about stainless steel is that it does not rust at all; it can in fact corrode, especially in environments near the sea with high humidity.

### Aluminium

Aluminum is a soft light metal that is silvery to gray in color. Depending on the alloy, aluminum usually has good corrosion resistance. It is common for the aluminum to be extruded into tubes or rolled into a plate in the desired material thickness.

### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

## Assembly and placement

**Surface mount**

Can be bolted above ground, to the floor or to a cast-in-place foundation. Bolts not included.

**Mounted to wall**

Bolted in place to stand/wall bracket.

Bolts for walls not included.

Fully assembled.

The wall-mounted version fastens with three M8 bolts measuring 10 mm x 30 mm and three washers measuring 10 mm x 21 mm. They are included in the delivery. The support post bolts to the surface with three 16 mm M8 bolts and three lockable nuts. They are included in the delivery. The post is prepared with two holes with a diameter of 13 mm for 12 mm bolts, which are not included.

**Maintenance****Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

**Powder coated Aluminium**

Products that are powder-coated can be touch-up painted with alkyd paint if necessary.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

**Character**

The Slingan ashtray spirals into an intriguing shape that can be emptied easily.

**Designers**

---

**Gunilla Hedlund**

