

Smidesstaket Modular Fencing System

Design Lars Gunnars

This classic steel fence resembles traditional forged steel, but it is made in pre-fabricated sections that are quick and easy to install. The metal is protected by a rust-resistant coating and a durable layer of polyurethane paint. The sections can be secured between ground-mounted posts. The timeless appeal of this simple style will seem contemporary for years to come.

Dimensions and weight

Individual dimensions

The fence posts: \emptyset 60 mm with a depth of 3 mm.

The gateposts: \emptyset 60 mm or \emptyset 120 mm with a depth of 3 mm.

Flat steel: 50 x 15 mm.

Fence filling round steel: \emptyset 16 mm.

Product numbers and combinations

Ö19-30	Fence C-C 180 cm.
Ö19-31	Fence C-C 120 cm.
Ö19-32	Fence C-C 90 cm.
Ö19-33	Fence C-C 238 cm.

Ö19-34 Double gate for fence, C-C 282 cm incl. 2 posts.Ö19-35 Single gate for fence, C-C 96 cm incl. 2 posts.

Ö19-36 Single gate for fence, C-C 96 cm incl. 2 posts. For wall mounting
 Ö19-37 Fitting section which can be cut on site to alternative dimensions 226,4 cm, 214,8 cm, 203,2 cm, 191,6 cm, 180,0 cm and 168,4 cm.

Ö19-40 End post.

Ö19-41 Middle post straight top.
Ö19-42 Middle post, angled top 90°.
Ö19-43 Middle post, angled top 135°.

Append to product number

VARIANTS

/90 = 90 cm total height above ground /110 = 110 cm total height above ground

INSTALLATION TYPE

M for in-ground.

Standard colours



Materials and surface treatments

TecTalis® rostskydd.

The fence is made in forged steel painted with TecTalis® corrosion protection and polyester powder coating in black RAL 9005.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

In-ground

Cast in ground.

Delivered in sections for assembly on site with M10 bolts.

Maintenance Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

Read more in our general maintenance advice at nola.se/en/care-and-

maintenance

Versions Available in three standard lengths: C-C 90 cm, C-C 120 cm, C-C 180 cm and C-

C 238 cm and in a choice of two heights (90 cm and 110 cm).

Character A flexible steel fence that resembles traditional metal railing. Constructed in pre-

fabricated sections, the fence is easy to install.

Designers

Lars Gunnars



