

nola®



Swing Ashtray

Design Jerry Hellström

Swing is a streamlined, functional ashtray free of ornamentation or decorative details. The circular base plate mounts laterally to a wall or post ready to receive ash and cigarette ends. The ashtray pivots downwards to empty the contents, eliminating the need for removable trays or grates. Swing's efficient design fits easily into areas where space is limited.

Dimensions and weight

Ashtray: Container: 15 cm x 15 cm x 15 cm Diameter of wall plate: 20 cm Weight: 3.3 kg

Ashtray with cover: Container: 15 cm x 15 cm x 15 cm Diameter of wall plate: 20 cm Weight: 4.4 kg

Cover: Length: 22 cm Width: 18 cm Weight: Appr 1.1 kg

Double ashtray with cover on post: Height: 120 cm Length: 44 cm Width: 18 cm Weight: 16 kg

Individual dimensions

The stainless steel/steel sheet used to make the container is 3 mm thick

The stainless steel/steel sheet used to make the wall plate is 4 mm thick

The post is made in stainless steel: 60 mm x 30 mm x 2 mm

Product numbers and combinations

Ö15-03 Swing askkopp utan tak. Rostfri.

Ö15-04 Swing askkopp med tak. Rostfri.

Append to product number

METAL SURFACE FINISH

S for black RAL 9005.

G for gray RAL 7011.

C for any color other than standard, starting cost is added.

INSTALLATION TYPE

V for mounted to wall.

Standard colours



RAL 9005

RAL 7011

Materials and surface treatments

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Stainless steel

Stainless steel is an iron alloy with at least 10.5% chromium that often has good resistance to corrosion (rust) and other chemical attacks. A common misconception about stainless steel is that it does not rust at all; it can in fact corrode, especially in environments near the sea with high humidity.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Assembly and placement

Mounted to wall

Bolted in place to stand/wall bracket.

Bolts for walls not included.

Delivered in parts for assembly on site.

Maintenance**Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

The single version can be wall-mounted. The double version can be mounted to a bollard or post. Both versions are available with or without a cover and are available in untreated stainless steel or steel powder-coated in standard colours grey or black.

Character

Swing is a streamlined, functional ashtray free of decorative details. Its efficient design fits easily into areas where space is limited.

Designers

Jerry Hellström

Architect, who started Design Torget in Stockholm. Has worked with product development for Nola since the 1990s, and is currently active as a designer.



