

nola®



Tuben Furniture Group

Design Gunilla Hedlund

The lightweight structure of these stackable designs gives them a breezy appearance that resonates with both modern architecture and open-air surroundings. The wooden slats provide a comfortable seat, while the tubular armrests give the seats the luxury of a recliner. Functional, yet fresh, these designs bring contemporary cool to any setting.

CERTIFICATION

Produkt listad i
Svanens Husportal  

Dimensions and weight

Individual dimensions

The frame is made in pipe steel: 25 mm x 2 mm

Wood components: 26 mm x 68 mm

Taben Armchair

Width: 70,5 cm

Height: 65,5 cm

Sitting height: 46 cm

Depth: 67,5 cm

Weight 15,5 kg

Taben table

Length: 130 cm

Width: 87 cm

Height: 73 cm

Weight 22 kg

Taben bench

Length: 160 cm

Width: 43,5 cm

Height: 52,5 cm

Weight 15,5 kg

Seat: 121 x 40,5 cm

Taben Park bench

Length: 184 cm

Width: 68 cm

Height: 94 cm

Sitting height: 46 cm

Weight 28 kg

Product numbers and combinations

U20-84 Taben armchair (only freestanding)

U20-71 Taben table

U20-72 Taben bench

U20-70 Taben backed bench

Append to product number

VARIANTS

V for white. RAL 9010 on steel and NCS S 0502-Y on wood (White).


G for green. RAL 6021 on steel and NCS S 3020-G20Y on wood (green).


C for any color other than standard, starting cost is added.

Standard colours

 RAL 9010

 RAL 6021

 NCS S 0502-Y (Vit)

 NCS S 3020-G20Y (grön)

Materials and surface treatments

Pine

Nola's pine is of high quality and comes from sustainable forestry. Pine is an environmentally friendly, domestically produced material. Damaged or untreated pine is quite easily attacked by decomposition processes; therefore, it is particularly important to repair damaged surfaces.

Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

Water-based glaze

Varnishing of wood is done with a water-based varnish. A water-based paint that is kinder to the environment. Under normal use, the paint has a good wear resistance and long durability.

Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

Assembly and placement

Freestanding

Freestanding product that is placed directly on the ground.

Fully assembled.

Freestanding. Attachable.

Maintenance

Glans 60. Pulverlack går att beställa på sprayflaska.

Water-based glazed pine

Products in varnished pine must be maintained regularly with alkyd paint. Maintenance intervals approximately 1 time per year. Damage and cracks should be repaired immediately. Touch-up paints in spray packaging are available in standard colors to order.

Powdercoated steel

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

Versions

The furniture group includes a bench, a backed bench a table and an armchair, all produced in standard colours greyish-green or white.

Character

These tubular designs bring contemporary cool to any setting. They appear chic enough to belong to the interior, yet they are made to be durable enough for the

outdoors.

Designers

Gunilla Hedlund



The Tuben furniture group, designed by Gunilla Hedlund. The lightweight structure of these stackable designs gives them a breezy appearance that resonates with modern buildings and the open-air

environments surrounding them.

