

nola®



## ZigZag Litterbin

Design Eva Herdin

The sides of the ZigZag litterbin are perforated with a repeating pattern of zigzag shapes, making it as lightweight as it is attractive. ZigZag corresponds to designs such as Kvadrat and can be paired with the ZigZag ashtray, giving it a wide range of combination possibilities.

CERTIFICATION



## Dimensions and weight

Height: 54 cm

Ø: 33 cm

Height including post: 81 cm

Volume: 42 L

Weight including wall bracket: 12 kg

Weight including post for casting in concrete: 15 kg

Weight concrete base: 23 kg

### Individual dimensions

The container is made of perforated 1 mm electro-galvanized, chromated, polyester powder-coated steel sheet.

The inner container is made of stainless steel.

Lid: 3 mm pressure-turned, natural anodized aluminum sheet.

The freestanding and attachable support posts and wall-hanging bracket are made of 3 mm sheet steel.

### ZigZag Ashtray

Height: 24 cm

Ø: 15 cm

### Ashtray

Height when attached to post: 80 cm

Weight: 2.5 kg

Weight post: 3,5 kg

### Rain cover

Overall height: 46 cm

Height above the ashtray: 22 cm

Width: 20 cm

### Individual dimensions

Sheath surface in herringbone-patterned, 1 mm electro-galvanized, chromated, polyester powder-coated steel sheet.

The anodised aluminium in the lid is 1.5 mm thick.

The perforated sheet steel in the container is 1 mm thick.

Post made of 3 mm edge-pressed sheet metal. Surface treatment like the basket.

The stainless steel in the rain cover is 3 mm thick.

## Product numbers and combinations

Ö16-64 ZigZag papperskorg med helt lock, inkl. stolpe med fotplatta för golvmontage.

Ö16-64M ZigZag papperskorg med helt lock, inkl. stolpe för fastgjutning i mark.

Ö16-64V ZigZag papperskorg med helt lock för väggmontage.

-

Ö16-65 ZigZag papperskorg med öppet lock + askkopp inkl. stolpe med fotplatta för golvmontage.

Ö16-65M ZigZag papperskorg med öppet lock + askkopp inkl. stolpe för fastgjutning i mark.

-

Ö16-66 ZigZag papperskorg med helt lock + askkopp, inkl. stolpe med fotplatta för markmontage.

Ö16-66M ZigZag papperskorg med helt lock + askkopp, inkl. stolpe för fastgjutning i mark.

-

Ö16-67 ZigZag papperskorg med öppet lock inkl. stolpe med fotplatta för golvmontage.

Ö16-67M ZigZag papperskorg med öppet lock inkl. stolpe för fastgjutning i mark.

Ö16-67V ZigZag papperskorg med öppet lock för väggmontage.

-

Ö16-63 Betongfot, fristående. Används tillsammans med stolpe med fotplatta.

Ö16-63S/90 Stolpfäste Ø: 90 mm. För papperskorgar ZigZag och Kvadrat.

Ö16-63S/108 Stolpfäste Ø: 108 mm. För papperskorgar ZigZag och Kvadrat.

Ö16-63S/121 Stolpfäste Ø: 121 mm. För papperskorgar ZigZag och Kvadrat.

Ö16-68 ZigZag askkopp inkl väggfäste.

Ö16-68RT Regntak till ZigZag askkopp.

Ö16-69 Stolpe till askkopp ZigZag med fotplatta för golvmontage.

Ö16-69M Stolpe till askkopp ZigZag för fastgjutning.

#### Standard colours

 RAL 7011

#### Materials and surface treatments

Materialspecifikation för askkopp: Se kategori Askkoppar.

##### Steel

Nola uses high-quality steel with good strength in our products. Steel rusts if left untreated and must therefore be surface treated.

##### Aluminium

Aluminum is a soft light metal that is silvery to gray in color. Depending on the alloy, aluminum usually has good corrosion resistance. It is common for the aluminum to be extruded into tubes or rolled into a plate in the desired material thickness.

##### Electrogalvanized

Electrogalvanizing (also known as zinc plating) provides corrosion protection through the sacrifice of zinc ions. It is created via a zinc coating on the steel using an electric current.

##### Powder coating

Powder coating is a coating that is applied as a free-flowing, dry powder. Unlike conventional liquid paint, powder coating is usually applied electrostatically and then cured under heat or with ultraviolet light. The result is an even, hard-wearing coloured surface with the desired gloss level.

#### Assembly and placement

Fully assembled.

The attachable version bolts to the post and the post bolts to the floor. The bolt-holes have a diameter of 10 mm for 8 mm bolts. Bolts not included.

The post for the ground-mounted version should be cast 40 cm below ground level.

The wall-mounted version should be bolted to the wall. The bolt-holes have a

diameter of 7 mm for 6 mm bolts. Bolts not included. Please refer to the assembly instruction for specific details.

#### Maintenance

##### **Powdercoated steel**

Products that are powder-coated can be touch-up painted with alkyd paint.

[Read more in our general maintenance advice at nola.se/en/care-and-maintenance](https://nola.se/en/care-and-maintenance)

#### Versions

Available with a round opening or hinged lid, and can be combined with an ashtray. The litterbin is made in a wall-mounted version or supplied with an attachable post that fits into a freestanding concrete base or can be cast into concrete.

#### Character

ZigZag is a low-profile, lightweight litterbin with a wide range of combination possibilities.

#### Designers

---

Eva Herdin

